



DECLARATION OF PERFORMANCE

No. 0003BauPVo 2013-07-14

1. Unique identification Code of the product type:
Single-axis hinges according to EN 1935-2002
2. Identification of the construction product, in accordance with article 11(4):

Two-Piece Door Hinge With Three Knuckle Design (Product listing see Annex)

CE-Classification see section 9. Declared performance and product listing

4	7	6	1	1	0*)	0**))	0***))
Category of use	Durability Grade	Test Door Mass	Fire/Smoke Suitability	Safety	Corrosion Resistance	Security	Hinge Grade

*) Class 1-4 depending on the material and surface, see section 9 and Annex A

**) Class 1 with optional locking pin "NRP"

***) see section 9 and product listing

3. For use on Doors and Windows
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)
Breuer & Schmitz GmbH & Co.KG
Locher Straße 25
42719 Solingen
GERMANY
5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)
See section 4
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V
System 1
7. The notified factory production control certification body SKH under EG-reference-No. 0502 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.
8. European Technical Assessment:
not applicable (see section 7)

9 . Declared performance:

Harmonised technical specification EN 1935:2002

Essential characteristics	Grade	Capability	
5.1 Initial friction torque measurements	Grade 1-7 Grade 8-11 Grade 12-14	maximum 2 Nm maximum 3Nm maximum 4Nm	
5.2 Static load 5.2.1 Load deformation	all Grades	Lateral deformation under load <2mm. Vertical deformation <4mm. Neither lateral nor vertical displacement exceeds to discharge the following values. Laterally <0.6mm; vertical <0.3mm Neither a material fraction still cracking is detected at normal or corrected visual examination	
5.2.2 Overload	all Grades	There are no breaks, cracks or deformation on hinge flaps, door hinges, connectors or pins, neither in normal nor in corrected visual examination detected The testing component has remained connected in during the test with the frame.	
5.3 Durability/ Shear strength	all Grades	There are no breaks, cracks or deformation on hinge flaps, door hinges, bushes or pins identifiable and the lateral deformation is not more than 3mm. After the check the additional vertical and lateral movements do not cross the measure of 1 mm. No breaks appear after 20 test cycles in hinge wings, hinges or pins.	
5.6 Hinges for use on fire-resistant and/or smoke-control doors	Grade 0	Not suitable	fire resistance
	Grade 1	Suitable for use on fire-resistant and / or smoke-control doors	
5.4 Durability	Grade 3	10000 test cycles	Cycles in continuous operation
	Grade 4	25000 test cycles	
	Grade 7	200000 test cycles	
5.8 Families of hinges with common design features	all Grades	These hinges have no deviation in the design nor in the materials used compared to the test pieces	
5.5 Corrosion resistance	Grade 0	no defined corrosion resistance	Corrosion resistance
	Grade 1	low corrosion resistance (24 hours)	
	Grade 2	moderate corrosion resistance (48 hours)	
	Grade 3	high corrosion resistance (96 hours)	
	Grade 4	very high corrosion resistance (240 hours)	
	Grade 5	exceptionally high corrosion resistance (480 hours)	
Dangerous substances	all Grades	The materials used in this product contain no hazardous materials. Furthermore they do not emit more of such materials to the environment than in any European standard or regulation.	

Additional features see Annex B

10. The performance of the product identified in section 1 and 2 is in conformity with the declared performance in section 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in section 4.

Signed for and on behalf of the manufacturer by:

Patrick Müller, managing Director

(Name of the signatory and function in the company)

Solingen, d. 11.05.2020



Annex:
Article listing to DoP
No. 0003BauPVo 2013-07-14

CE-classification see section 9. Declared performance

(RD) HL 800 102x76
 102x89
 102x102
 114x84
 114x102
 114x114
 002-130
 002-132
 002-129
 002-128
 002-150

4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14
4	7	7	1	1	0*)	1	14

*)Class 1 - 4 each on the material and surface, see section 9 and Annex A

(V) RD 818 89 x 80
 89 x 89
 89 x 102
 89 x 127
 89 x 152

4	7	6	1	1	0*)	0**))	13
4	7	6	1	1	0*)	0**))	13
3	7	6	1	1	0*)	0**))	11
3	7	4	1	1	0*)	0**))	11
3	7	4	1	1	0*)	0**))	11

*)Class 1 - 4 each on the material and surface, see section 9 and Annex A

**) Class 1 for version "V" burglar test SKG

(V) RD 818 DD 89 x80
 89 x 89

4	7	6	1	1	0*)	0**))	13
4	7	6	1	1	0*)	0**))	13

*)Class 1 - 4 each on the material and surface, see section 9 and Annex A

**) Class 1 for version "V" burglar test SKG

JS (V) RD 818 89 x80
 89 x 89

4	7	6	1	1	0*)	0**))	13
3	7	4	1	1	0*)	0**))	11

*)Class 1 - 4 each on the material and surface, see section 9 and Annex A

**) Class 1 for version "V" burglar test SKG

P RD 818 89x80
 89x89
 89x102
 89x127
 89x152

4	7	6	1	1	0*)	1	13
4	7	6	1	1	0*)	1	13
4	7	6	1	1	0*)	1	13
3	7	4	1	1	0*)	1	11
3	7	4	1	1	0*)	1	11

*) Class 1 - 4 each on the material and surface, see section 9 and Annex A

SKG ** Certificat 487.642.06 and .07

(RD 804) 102 x 76 mm
 102 x 89 mm
 102 x 102 mm
 114 x 89 mm
 114 x 102 mm
 114 x 114 mm
 127 x 64 mm
 127 x 89 mm
 127 x 102 mm
(002-217) 127 x 127 mm

4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14

*) Class 1 - 4 each on the material and surface, see section 9 and Annex A

**) Class 1 for optional locking pin "NRP"

(RD) 805

4	7	7	1	1	0*)	0**))	14
---	---	---	---	---	-----	--------	----

*) Class 1 - 4 each on the material and surface, see section 9 and Annex A

**) Class 1 for optional locking pin "NRP"

002-195
 002-196
 002-197
 002-198
 002-199
 002-201
 002-204
 002-205 (V)
 002-206
 002-207
 002-208
 002-209
 002-211
 002-213
 002-214
 002-218
 002-219

4	7	6	1	1	0*)	0**))	13
4	7	7	1	1	0*)	0**))	14
3	7	4	1	1	0*)	0**))	11
3	7	4	1	1	0*)	0**))	11
3	7	4	1	1	0*)	0**))	11
4	7	6	1	1	0*)	0**))	13
4	7	6	1	1	0*)	0**))	13
4	7	6	1	1	0*)	0**))	13
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	6	1	1	0*)	0**))	13
4	7	6	1	1	0*)	0**))	13
4	7	7	1	1	0*)	0**))	14
4	7	7	1	1	0*)	0**))	14
4	7	6	1	1	0*)	0**))	13
4	7	6	1	1	0*)	0**))	13

002-220	3	7	4	1	1	0*)	0**))	11
002-221	3	7	4	1	1	0*)	0**))	11
002-223	4	7	6	1	1	0*)	0**))	13
002-224	4	7	6	1	1	0*)	0**))	13
002-225	3	7	4	1	1	0*)	1	11
002-227	4	7	7	1	1	0*)	0**))	14
002-228	3	7	4	1	1	0*)	0**))	11
002-229	4	7	7	1	1	0*)	0**))	14
002-230	4	7	7	1	1	0*)	0**))	14
002-231	4	7	6	1	1	0*)	0**))	13
002-232	4	7	6	1	1	0*)	0**))	13
002-236	4	7	7	1	1	0*)	0**))	14
002-239	4	7	7	1	1	0*)	0**))	14
002-240	4	7	7	1	1	0*)	0**))	14
VZK/VZX 804	3	7	6	1	1	0*)	0**))	13
RD 804-3D	3	7	6	1	1	0*)	0**))	13
002-237	3	7	4	1	1	0*)	0**))	11
002-241	3	7	4	1	1	0*)	0**))	11
002-247	3	7	4	1	1	0*)	0**))	11

*) Class 1 - 4 each on the material and surface, see section 9 and Annex A

**) Class 1 for optional locking pin "NRP"

(V) RD 1815	89 x 80	3	7	4	1	1	0*)	0**))	11
	89 x 89	3	7	4	1	1	0*)	0**))	11

*) Class 1 - 4 each on the material and surface, see section 9 and Annex A

**) Class 1 for optional locking pin "NRP"

(V) RD 1816	89 x 80	3	7	4	1	1	0*)	0**))	11
-------------	---------	---	---	---	---	---	-----	--------	----

*) Class 1 - 4 each on the material and surface, see section 9 and Annex A

**) Class 1 for optional locking pin "NRP"

NRP 4000	4	7	7	1	1	0*)	0	14
NRP 4020	4	7	7	1	1	0*)	0	14

*) Class 1 - 4 each on the material and surface, see section 9 and Annex A

Annex A

Corrosion resistance of surfaces in accordance
with DIN EN 1670

Surface	Designation	Class
Stainless Steel AISI 316	STX	5
Stainless Steel AISI 304	STD, ST	4
Powdercoated	WE, BL, GV-K	4
Accoya-coating	GVC-R	4
White Zinc Plated	GV, GV-R	3
Yellow Zinc Plated	GVG, GVG-MS	3
Zinc Plated Colour Alu F1	GV-F1	3
Polished Brass	S	2
Brassed Polished	WF	2
Gold Plated	GFG	2
Chrome polished	CMP	2
Chrome mat	CMD	1
Nickel Plated	ND	1

Classification

Class 1	24h	salt spray test
Class 2	48h	salt spray test
Class 3	96h	salt spray test
Class 4	240h	salt spray test
Class 5	480h	salt spray test

Unlisted surface finishes do not serve the corrosion protection,
they serve only optical aspects.

checked by: SHR Hout Research

report No. 3357-K1 vom 18. januar 2004

Annex B
Harmonised technical specification EN 1935:2002

Additional features	Grade	Capability			Category of use	
Usage	Grade 1	<u>Light duty:</u> Hinges for use on doors or windows in housing or other living areas and in buildings where there is a low frequency of use. (nonpublic access).				
	Grade 2	<u>Medium duty:</u> Hinges for use on doors in housing or other living areas and in other buildings where there is a medium frequency of use. (limited public access).				
	Grade 3	<u>Heavy duty:</u> Hinges for use on doors in buildings where there is a high frequency of use. (public access).				
	Grade 4	<u>Severe duty:</u> Hinges for use on doors where extreme levels of use and misuse are anticipated. (public access points to the likelihood of abuse).				
Test door maas & Hinge grade	Grade 0 Grade 1 Grade 1 Grade 1 Grade 2 Grade 2 Grade 2 Grade 3 Grade 3 Grade 3 Grade 4 Grade 5 Grade 6 Grade 7	max. 10 Kg max. 20 Kg max. 20 Kg max. 20 Kg max. 40 Kg max. 40 Kg max. 40 Kg max. 60 Kg max. 60 Kg max. 60 Kg max. 80 Kg max. 100 Kg max. 120 Kg max. 160 Kg	Test door maas		Grade 1 Grade 2 Grade 3 Grade 4 Grade 5 Grade 6 Grade 7 Grade 8 Grade 9 Grade 10 Grade 11 Grade 12 Grade 13 Grade 14	
4.6 Safety	Grade 1					
4.8 Security	Grade 0 Grade 1	Not suitable to burglar-proof doors. Following evaluation of the suitability for burglary, suited to each intrusion-resistant doors.				